



Uniglide FRC is a Metal Treatment Oil Concentrate that gives protection to engines, differentials & gearboxes.

ADVANTAGES

- FRC mixes with mineral and synthetic oils.
- Adds a protective coating to all metal surfaces.
- Extends the life of the equipment treated by reducing friction, temperature and wear.
- Higher oil pressure.
- Suitable for gasoline, diesel & CNG engines.
- Used in manual and automatic transmissions.
- Better power delivery.
- Provides cold start protection.

SPECIAL INSTRUCTIONS

- **DO NOT ADD TO ENGINES THAT HAVE NOT BEEN RUN IN.** (Suggest 5000km or 250 hours)
- Can **NOT** repair damaged or worn metal surfaces.

RECOMMENDED DOSAGE

- Add 10% FRC to car or truck crankcase 1st oil change. Reduce to 5% for following oil changes.
- 10% FRC to manual gearboxes every oil change.
- 5% in automatic gearboxes every oil change.
- 5% FRC in motorcycles with a wet clutch every oil change.
- 10% FRC in differentials. **(NOT FOR CLUTCH-TYPE LSD!)**

SAFETY

Keep out of reach of children. Wash hands after use. Do not swallow. If poisoning occurs, do NOT induce vomiting and contact a doctor. Show medical staff the label.

FIRE

Use dry foam or CO² to extinguish.

SEE THE SDS FOR ADDITIONAL INFORMATION IN TRANSPORT
EMERGENCY DIAL +91 729 000 2525 POLICE OR FIRE BRIGADE

FRICTION REDUCING
CONCENTRATE

PERFORMANCE
FROM TECHNOLOGY

REDUCE FRICTION • REDUCE HEAT
REDUCE WEAR & TEAR • EXTEND ENGINE LIFE



275 ml



Performance Lubricants India (P)
582, Sector 8, IMT Manesar Gurugram
(Haryana) 122052 INDIA

info@performancelubricants.in
www.performancelubricants.in

Product from
Uniglide Lubricants, Australia
PO Box 266, Nightcliff NT 0810
Australia

275 ml
UFRC275

MRP ₹
(Incl. of all taxes)
Batch No. :
MFG. Date :
Net Quantity :

