



## MULTISPRAY

BEST ALL-PURPOSE PENETRATING SPRAY  
FOR INDUSTRIAL, MACHINING, AUTOMOTIVE  
AND DOMESTIC USE.

25-35% saturated hydrocarbons, chloro hydrocarbons. Distillates, Petroleum,  
hydrotreated light naphthenic. Balance Ingredients determined to be Non-Hazardous



**INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND  
INHALING CONTENTS CAN BE HARMFUL OR FATAL**

300g/400ml

## MULTISPRAY

Advanced formulation lubricates whilst penetrating and forming a  
long-lasting protective film on any metal surface.  
Contains **UNIGLIDE'S** unique **FRC** for Performance from Technology.

A LIGHT APPLICATION WILL ASSIST WITH  
THE FOLLOWING BENEFITS:

- Penetrating oil for releasing rusted & seized bolts & studs.
- Protects against corrosion, acids & the environment.
- Moisture dispersant for all electrical switchgear.
- Excellent metal cutting fluid for thread tapping, drilling, broaching etc.
- Effective lubricant for motorcycle, bicycle & other chains.
- Loosens chemical thread locking compounds.



USER  
FRIENDLY  
FORMULA  
POWERED BY  
CO<sub>2</sub>

### AND HUNDREDS OF OTHER USES!

**SAFETY:** Keep out of reach of children. Read label & special instructions before use. Do not inhale in any form use thorough personal hygiene. Avoid contact during pregnancy/while nursing. **FIRE:** If involved in a fire use water fog, fine water spray, alcohol resistant foam, standard foam, dry agent (carbon dioxide or powder). **FIRST AID:** If poisoning occurs, contact a doctor or Poisons Information Centre. If medical advice is needed, have product container or label at hand. **SWALLOWED:** If swallowed do NOT induce vomiting. Give a glass of water. Seek medical assistance. **EYE:** If in eyes, hold eyes open, flush with water for at least 15 minutes. See a doctor. **SKIN:** If skin contact occurs, remove contaminated clothing and wash skin thoroughly. If irritation occurs seek medical advice. **INHALED:** Remove from contaminated area. Seek medical advice.

#### DIRECTIONS:

- Spray onto area to be treated.
- Avoid breathing vapour.
- Use with adequate ventilation.
- If badly rusted, and for chemical thread locking compounds - allow to penetrate a while before applying force.

SEE THE SDS FOR ADDITIONAL  
INFORMATION IN TRANSPORT

EMERGENCY DIAL +91 729 000 2525  
POLICE OR FIRE BRIGADE



**SHAKE WELL BEFORE USE**

300g/400ml

UMS300

PERFORMANCE LUBRICANTS INDIA (P) Ltd

582, SECTOR 8, IMT MANESAR GURGAON

122052 (HARYANA) INDIA

info@performancelubricants.in

www.performancelubricants.in

https://www.facebook.com/Performance-Lubricants-India-Pvt-Ltd-108185654273082/



**MRP ₹**  
(Incl. of all taxes)  
**Batch No. :**

**MFG. Date :**  
**Net Quantity :**