



PL-40 SPRAY

ALL-PURPOSE PENETRATING & LUBRICATING
SPRAY FOR INDUSTRIAL, MACHINING,
AUTOMOTIVE & DOMESTIC USE.

25-35% saturated hydrocarbons, chloro hydrocarbons, Distillates, Petroleum,
hydrotreated light naphthenic, Balance Ingredients determined to be Non-Hazardous



INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING
AND INHALING CONTENTS CAN BE HARMFUL OR FATAL.

112g/150ml

PL-40 SPRAY

Advanced formulation lubricates whilst penetrating and forming a long-lasting protective film on any metal surface.
Contains **UNIGLIDE'S** unique **FRC** for Performance from Technology.

A LIGHT APPLICATION WILL ASSIST
THE FOLLOWING BENEFITS:

- Penetrating oil for releasing rusted & seized nuts, bolts &
- Protects against corrosion, acids & the environment.
- Moisture dispersant for all electrical switchgear.
- Excellent metal cutting fluid for thread tapping, drilling, broaching, etc.
- Effective lubricant for motorcycle, bicycle & other chains.
- Loosens chemical thread locking compounds.

AND HUNDREDS OF OTHER USES!

SAFETY: Keep out of reach of children. Read label & special instructions before use. Do not inhale in any form use through personal hygiene. Avoid contact during pregnancy/while nursing. **FIRE:** If involved in a fire use water fog, fine water spray, alcohol resistant foam, standard foam, dry agent (carbon dioxide or powder). **FIRST AID:** If poisoning occurs, contact a doctor or Poisons Information Centre. If medical advice is needed, have product container or label at hand. **SWALLOWED:** If swallowed do **NOT** induce vomiting. Give a glass of water. Seek medical assistance. **EYE:** If in eyes, hold eyes open, flood with water for at least 15 minutes. See a doctor. **SKIN:** If skin contact occurs, remove contaminated clothing and wash skin thoroughly. If irritation occurs seek medical advice. **INHALED:** Remove from contaminated area. Seek medical advice.

DIRECTIONS:

- Spray onto area to be treated.
- Avoid breathing vapour.
- Use with adequate ventilation.
- If badly rusted, and for chemical thread locking compounds - allow to penetrate a while before applying force.

SEE THE SDS FOR ADDITIONAL
INFORMATION IN TRANSPORT
EMERGENCY DIAL +91 729 000 2525
POLICE OR FIRE BRIGADE



SHAKE WELL BEFORE USE

112g/150ml

UPL150

PERFORMANCE LUBRICANTS INDIA (P) Ltd

582, SECTOR 8, IMT MANESAR GURGAON

122052 (HARYANA) INDIA

info@performancelubricants.in

www.performancelubricants.in

https://www.facebook.com/Performance-Lubricants-India-Pvt-Ltd-108185654273082/

MRP ₹
(Incl. of all taxes)
Batch No. :

MFG. Date :

Net Quantity :

